OpenEye®

OE-C1015D5-S

5MP Indoor Micro IP Dome Camera

Equipped with analytics and a 3mm fixed lens, the OE-C1015D5-S delivers high quality, 5MP video in a discreet dome design.



5MP
Experience clear imagery with 5MP resolution, boosting your video quality.

Advanced Analytics
Get a more intelligent & aware solution with advanced analytics processing.

Adaptive IR
Optimal illumination & clear images in low-light environments.

True Wide Dynamic Range
Quickly adapt to shifting light for consistent, high-quality imagery.

Audio I/O
Enhance video surveillance with clear sound capture and playback.

Specifications

General	
Housing/Dome Cover	Metal & Polycarbonate
Ingress Protection	N/A
Impact Rating	N/A
Dimensions	Ø4.25" x 2.93" (Ø108 x 74.5mm) Camera only | Ø4.25" x 3.05" (Ø108 x 77.5mm) w/ Adapter Plate
Weight	0.86 lbs (392g)
Alarm In/Relay Out	1/1 (terminal)
Pan/Tilt/Rotate	**Pan:** 0–355° **Tilt:** 0–60° **Rotate:** 0–360°
Country of Origin	Taiwan
NDAA Compliant	Yes

Image	
Image Sensor	1/2.8" 5MP Sony Progressive Scan CMOS
Shutter	Auto/Manual, 1/3 ~ 1/13,000s
Lens	3.0mm Fixed
Max Resolution	2592x1944
Aspect Ratio	4:3
Field of View	97°
Remote Focus/Zoom	N/A
Day/Night	True Day/Night with IR-Cut Filter
Wide Dynamic Range (WDR)	True WDR
IR	Up to 65'
Analytics	Person, Vehicle, and Line Crossing Analytics

Video Control	
Configurable Video Profiles	N/A
Video Streams	3
Compression	H.264, MJPEG
Max Frame Rate	Primary Stream: 30FPS @ 2592x1944
Day/Night	Auto/Day/Night/Schedule
White Balance	Auto/Manual
OSD	Up to 4 OSDs
ROI	Up to 5 Areas
Motion Detection	Up to 4 Areas
Privacy Masking	Up to 4 Areas
Image Rotation	Flip Vertical, Flip Horizontal, 90° Clockwise

Audio	
Audio In/Out	1/1
Compression	G.711A, G.711U
Two-Way Audio	Yes
Suppression	N/A

Illumination	
White Light Illumination	N/A

Specifications

Network	
Connector	RJ45
Network	10/100Mbps


Power	
Power Consumption	Max 6.5W
Power Source	PoE 802.3af

Environmental	
Operating Temperature	-4°F ~ 122°F (-20°C ~ 50°C)(IR ON) -4°F ~ 140°F (-20°C ~ 60°C)(IR OFF)
Humidity	90% RH (Non-condensing)


Storage	
Onboard Storage	MicroSD Card, Up to 1TB
Network	N/A

Certifications	
Certifications	CE, FCC, TAA, UL, UKCA

Dimensions



Connections



1	Reset Button	-	To restore the camera to factory defaults: 1. Disconnect power for 30 seconds. 2. Reconnect power and wait 30 seconds. 3. Press and hold the reset button for 20 seconds.
2	microSD Card Slot	-	Insert the microSD card into the slot to store videos and snapshots
3	Alarm & Audio I / O	1	Line Out -
		2	Line Out +
		3	Line In -
		4	Line In +
		5	Alarm Output -
		6	Alarm Output +
		7	Alarm Input -
		8	Alarm Input +
4	RJ-45	-	For network and PoE connections

Accessories






10-Series Wall Mount
OE-CA10WM-01



10-Series Junction Box
OE-CA10JB-01



10-Series Pendant Cap
OE-CA10PC-01

Accessory Kits



10-Series Wall Mount Kit
with Outdoor Junction Box
OE-CA10WMKIT-01



10-Series Wall Mount
OE-CA10WM-01



Indoor/Outdoor 7” Junction Box
OE-CA00JB-01



10-Series Pole Mount Kit
with Outdoor Junction Box
OE-CA10PMKIT-01



10-Series Wall Mount
OE-CA10WM-01




Indoor/Outdoor 7” Junction Box
OE-CA00JB-01



Pole Mount Kit
OE-CA00PMK-01



10-Series Wall Mount Kit
with Pendant Cap
OE-CA10WMKIT-02




10-Series Pendant Cap
OE-CA10PC-01



Indoor/Outdoor Wall Mount
OE-CA00WM-01




10-Series Corner Mount Kit
with Pendant Cap
OE-CA10CMKIT-01



10-Series Pendant Cap
OE-CA10PC-01




Indoor/Outdoor Wall Mount
OE-CA00WM-01



Corner Mount
OE-CA00CM-01



10-Series Pole Mount Kit
with Pendant Cap
OE-CA10PMKIT-02



10-Series Pendant Cap
OE-CA10PC-01




Indoor/Outdoor Wall Mount
OE-CA00WM-01



Pole Mount Kit
OE-CA00PMK-02



10-Series Ceiling Mounted Pole Kit
with Pendant Cap
OE-CA10CPKIT-01



10-Series Pendant Cap
OE-CA10PC-01



Ceiling-Mounted Pole
OE-CA00CMP-01

Copyright ©2026 OpenEye. All Rights Reserved. Information contained in this document is subject to change without prior notice. OpenEye does its best to provide accurate information but cannot be held responsible for typos or mistakes.