

# 600-SERIES - 3MP IP DOME CAMERA

# OE-C6123 / W2 / W3 / W6 / W12



The OE-C6123-W indoor 3MP IP micro dome camera provides high quality images at 3MP max resolution. This camera uses True WDR to balance contrast between high and low light. The OE-C6123-W also has 3-axis gimbal positioning to allow placement on either a ceiling or a wall.

The OE-C6123-W has a compact design with an angled CAT 5 port, which allows connection of IP cables with larger molded heads. This camera operates using PoE, which requires only a single cable for both power and video.

All OpenEye IP cameras are fully ONVIF<sup>™</sup> compliant and are compatible with the OpenEye Web Services platform, allowing multiple users to view high quality images and perform remote setup using a Web browser.

### **FEATURES**

- 3MP maximum resolution
- True Wide Dynamic Range @ 2MP
- MJPEG / H.264 video compression
- 3-axis gimbal
- 1/3" Progressive image sensor
- ONVIF<sup>™</sup> Profile S compliant



www.openeye.net

# **SPECIFICATIONS**

CAMERA			
Part Number	OE-C6123 / W2 / W3 / W6 / W12		
Maximum Resolution	3MP		
Image Sensor	1/3" Progressive CMOS		
Video Compression	H.264 / MJPEG		
Frame Rate	25 / 30 IPS @ 3MP H.264		
ONVIF	Profile S		
Streaming	Up to 4 simultaneous streams		
Field of View	2.3mm fixed: 125° 3.6mm fixed: 71.8° 6mm fixed: 46° 12mm fixed: 28°		
Browser Support	Internet Explorer (6.0+) / Chrome / Firefox / Safari		
Wide Dynamic Range	Shutter WDR on / off @ 2MP		
White Balance	Auto / Manual / ATW / One Push		
Auto White Balance Range	On / Off		
Auto Gain Control	Yes		

#### ENVIRONMENTAL

**Operating Temperature** 

131	°F (-2	~ 0	55	°C)

POWER		
Power Consumption	3.64W .6W w/SD card	
Input Voltage	12vDC / 24vAC / PoE	
PoE Class	2	

-4 ~

	,	
PHYSICAL		
microSD Card Slot	SDXC 64GB support	
Alarm In / Out	4-pin terminal block	
Audio In / Out	2-pin terminal block	
Camera Weight	.44lb (200g)	
Dimensions	ø4.13 x 2.04in (ø105 x 52mm)	
Housing / Dome Cover	Plastic housing	

## **ACCESSORIES**

#### OE-CA6000APM

600 / 6000-series Pendant Cap Adapter Plate for OE-C6123

OE-CA6000PMG 6000 / 9000-series Indoor Gooseneck Wall Mount Kit\*

OE-CA6000PMW 6000 / 9000-series Indoor Low Profile Wall Mount Kit\*

OE-CA6000PMK 6000 / 9000-series Indoor Pendant Cap\*

OE-CA611WM 600 / 6000-series Indoor Wall Mount\*

\*requires OE-CA6000APM





### DIMENSIONS

#### FRONT VIEW









#### 34846AA

Copyright ©2016 OpenEye. All Rights Reserved. Information contained in this document is subject to change without prior notice. OpenEye does its best to provide accurate information but cannot be held responsible for typos or mistakes.



23221 E Knox Ave 509.232.5261

