




**TRUE WDR**

True Wide Dynamic Range ensures clear video even in installations with high-contrast areas



**ALARM I/O**

Alarm connections wire the camera directly to alarm devices



**ADAPTIVE IR LEDs**

Adaptive IR technology for clear pictures in total darkness



**TRUE DAY / NIGHT**

True Day / Night provides superior video in a variety of lighting



**TWO-WAY AUDIO**

Receive and transmit audio through the camera



**NDAA COMPLIANT**

NDAA compliance meets the latest federal security standards

## CAMERA SPECIFICATIONS

IMAGE	
Image sensor	1/1.7" Sony Progressive CMOS
Shutter	Auto/Manual; 1 ~ 1/100000s
Lens	1.65mm Fixed
Max Resolution	<b>Software Dewarping:</b> 4000x3000 <b>Edge Dewarping:</b> 2976x2976
Aspect Ratio	16:9
Field of View	180°
Day/Night	True Day / Night w/ IR-Cut Filter
Wide Dynamic Range (WDR)	True WDR @ 12MP; 120db
IR	Up to 16'

VIDEO CONTROL	
Video Streams	4
Compression	H.264 / H.265 / MJPEG
Max Frame rate	12MP @ 20FPS
Day/Night	Auto / Manual / Light Sensor
White Balance	Auto / Manual / Smart
ROI	Up to 3 areas
Motion Detection	Up to 4 areas
Privacy Masking	Up to 5 areas

AUDIO	
Audio In/Out	1 - Line In, 1 - Line Out
Compression	uLAW, AAC
Two-way Audio	Yes


NETWORK	
Connector	RJ45
Network	10/100/1000 Mbps
ONVIF®	Profile S / G / Q / T Compliant

HARDWARE	
Housing / Dome Cover	Metal / Polycarbonate
Ingress Protection	IP66
Impact Rating	IK10
Dimensions	Ø5.1" x 2.3" (Ø130 x 58mm)
Weight	1.2lb (0.565kg)
Alarm In / Relay Out	1 / 1
Country of Origin	Taiwan
NDAA Compliant	Yes


## CAMERA SPECIFICATIONS (CONTINUED)

POWER	
Power Consumption	PoE: Max 12.95W 12vDC: Max 11.16W
Power Source	PoE (IEEE 802.3af) / DC 12V±25%
ENVIRONMENTAL	
Operating Environment	-22°F ~ 131°F (-30°C ~ 55°C)
Humidity	≤90% RH (non-condensing)
STORAGE	
Onboard Storage	Up to 512GB MicroSD card
Network	FTP, NAS
CERTIFICATIONS	
Safety	UL / CE / RCM
EMC	FCC Class A

## DIMENSIONS



## CONNECTIONS



1	RJ-45	For network and PoE connections	
2	Audio I/O	Pink	Audio In (Line In)
		Green	Audio Out (Line Out)
3	Power (12vDC)*	Black	DC 12V -
		Red	DC 12V +
4	Alarm I/O	1	Alarm In -
		2	Alarm In +
		3	Alarm Out -
		4	Alarm Out +

\*12vDC power input port should be plugged when not in use.


# ACCESSORIES



91-Series Angled Wall Mount  
**OE-CA91AWM-01**



91-Series Adapter Plate  
**OE-CA91AP-01**



91-Series Adapter Plate  
**OE-CA91AP-01**



Wall Mount  
**OE-CA79WM**

91-Series Wall Mount Kit  
**OE-CA91WMKT-01**



91-Series Adapter Plate  
**OE-CA91AP-01**



Dome Junction Box  
**OE-CA79JB**

91-Series Junction Box Kit  
**OE-CA91JBKT-01**



91-Series Adapter Plate  
**OE-CA91AP-01**




Pendant Mount Adapter  
**OE-CA79PM**

91-Series Pendant Mount Kit  
**OE-CA91PCKT-01**



91-Series Wall Mount Kit  
**OE-CA91WMKT-01**



Indoor/Outdoor 7" Junction Box  
**OE-CA00JB-01**



91-Series Pendant Mount Kit  
**OE-CA91PCKT-01**



Ceiling-Mounted Pole  
**OE-CA00CMP-01**



91-Series Pendant Mount Kit  
**OE-CA91PCKT-01**



Indoor/Outdoor Wall Mount  
**OE-CA00WM-01**



91-Series Pendant Mount Kit  
**OE-CA91PCKT-01**



Indoor/Outdoor Wall Mount  
**OE-CA00WM-01**



Corner Mount  
**OE-CA00CM-01**



91-Series Pendant Mount Kit  
**OE-CA91PCKT-01**



Indoor/Outdoor Wall Mount  
**OE-CA00WM-01**



Pole Mount Kit  
**OE-CA00PMK-02**