




TRUE DAY / NIGHT

True Day / Night provides superior video in a variety of lighting conditions



ALARM I/O

Alarm connections wire the camera directly to alarm devices



TRUE WDR

True Wide Dynamic Range ensures clear video even in installations with high-contrast areas



TWO-WAY AUDIO

Receive and transmit audio through the camera



REMOTELY REPOSITIONABLE

Remotely repositionable camera lenses move left to right on a track, can tilt up/down and zoom



NDAA COMPLIANT

NDAA compliance meets the latest federal security standards

CAMERA SPECIFICATIONS

IMAGE	
Image sensor	20MP, 4x 1/2.8", 5MP CMOS Progressive Sensor
Shutter	Auto/Manual; 1/7 ~ 1/20000
Lens	2.7~13.5mm motorized autofocus lens
Max Resolution	2592x1944
Aspect Ratio	4:3
Field of View	103° ~ 34°
PTZ	Remotely adjustable: Pan 360°, Tilt 90°, 4x Zoom
Day/Night	True Day / Night w/ IR-Cut Filter
Wide Dynamic Range (WDR)	True WDR
IR	131'

VIDEO CONTROL	
Video Streams	3 per Image Sensor
Compression	H.264
Max Frame rate	30FPS
Day/Night	Auto / Day / Night
White Balance	Auto / Manual
OSD	Up to 4 per sensor
ROI	Up to 5 per sensor
Motion Detection	Up to 5 per sensor
Privacy Masking	Up to 5 per sensor
Image Rotation	Flip Vertical, Flip Horizontal

AUDIO	
Audio In/Out	1 / 1
Compression	G.711A, G.711U
Two-way audio	Yes
Suppression	Yes

NETWORK	
Connector	RJ45
Network	10/100Mbps
ONVIF®	Profile S / G / T Compliant

CAMERA SPECIFICATIONS (CONTINUED)

HARDWARE	
Housing / Dome Cover	Cast Aluminum
Ingress Protection	IP66
Impact Rating	IK10
Dimensions	13.9" x 13.9" x 11.6" (352 x 352 x 295mm)
Weight	7.5lb (3.4kg)
Alarm In / Relay Out	1 / 1 (Wet Contacts)
Country of Origin	Taiwan
NDA Compliant	Yes


POWER	
Power Consumption	Max 40W (IR On) (PoE Injector Included)
Power Source	24V DC / 24V AC / PoE++ Class 5 (IEEE 802.3bt)

ENVIRONMENTAL	
Operating Environment	-40°F ~ 131°F (-40°C~55°C) (IR OFF)
Humidity	≤90% RH (non-condensing)


STORAGE	
Onboard Storage	2x MicroSD card; Up to 512GB
Network	Supported

CERTIFICATIONS	
Certifications	UL / CE / FCC Class A / RCM

DIMENSIONS



CONNECTIONS



1	Power (12vDC)	Red	24vDC +
		White	GND -
2	Audio I / O	Red	Audio Out +
		Black	Audio Out -
	Audio I / O	Red	Audio In +
		Black	Audio In -
3	Alarm I / O	Red	Alarm Out +
		Purple	Alarm Out -
		Orange	Alarm In +
		Black	Alarm In -

INCLUDED ACCESSORIES

- 1.5" Threaded Pendant Cap
- 60W PoE Injector

ACCESSORIES



Indoor/Outdoor Wall Mount
OE-CA00WM-01



Ceiling-Mounted Pole
OE-CA00CMP-01



Indoor/Outdoor Wall Mount
OE-CA00WM-01



Corner Mount
OE-CA00CM-01



Indoor/Outdoor Wall Mount
OE-CA00WM-01



Pole Mount Kit
OE-CA00PMK-02