




OE-MV



OE-MD GEN 3



OE-MT GEN 2



OE-MM GEN 2



OE-MK GEN 4



OE-MH GEN 3

	OE-MV	OE-MD	OE-MT	OE-MM	OE-MK	OE-MH	
RECORDING	Max Channels	24	32	32 / 96*	JBOD: 64 / 96 RAID: 64 / 128*	JBOD: 96 RAID: 128	
	Built-In Ports	-	8 or 16 PoE Ports	-	-	-	
	Max Recording Rate	100Mbps	150Mbps	300Mbps	JBOD: 300 Mbps RAID: 400 Mbps	JBOD: 300 Mbps RAID: 400 Mbps	
CONNECTIONS	Audio Support	IP Camera Audio (dependent on camera)	IP Camera Audio (dependent on camera)	IP Camera Audio (dependent on camera)	IP Camera Audio (dependent on camera)	IP Camera Audio (dependent on camera)	
	Video Outputs	2 x HDMI®	1 x HDMI®, 1 x Display Port	1 x HDMI®, 1 x DisplayPort, 1 x VGA	1 x HDMI®, 2 x DisplayPort, 1 x D-SUB	1 x HDMI®, 2 x DisplayPort, 1 x D-Sub	
	Maximum Display Resolution	4K	4K (HDMI®) / 4096x2160 (DP)	4K (HDMI®) / 4096 x 2160 (DP) / 1080P (VGA)	4K (HDMI®) / 4096 x 2160 (DP) / 1080P (D-Sub)	4K (HDMI®) / 4096 x 2160 (DP) / 1080P (D-Sub)	
	Dedicated Client Network	Yes	Yes	Yes	Yes	Yes	
	Dedicated Camera Network	Yes	Yes	Yes	Yes	Yes	
	Alarm Sensor Inputs	-	-	4 x Form A contacts	4 x Form A contacts (optional)	4 x Form A contacts (optional)	4 x Form A contacts (optional)
	Digital Relay Outputs	-	-	4 x Form A contacts	4 x Form A contacts (optional)	4 x Form A contacts (optional)	4 x Form A contacts (optional)
	USB Ports	Front: 2 x USB 3.0 Rear: 2 x USB 3.0	Front: 2 x USB 2.0 Rear: 2 x USB 3.0	Front: 2 x USB 3.0 ports Rear: 4x USB 3.2 Gen 1, 2x USB 2.0	Front: 2 x USB 3.0 ports Rear: 1 x USB Type-C (with USB 3.2 Gen 2 support) 3 x USB 3.2 Gen 1, 2 x USB 2.0		
	Operating System	Linux	Linux	Linux (standard) / Windows (optional)*	JBOD: Linux (Windows optional) RAID: Microsoft Windows	Microsoft Windows	Microsoft Windows
	Video Signal Loss Detection	Yes	Yes	Yes	Yes	Yes	Yes
Server Side Motion Detection	Yes	Yes	Yes	Yes	Yes	Yes	
SOFTWARE	Remote Operation	Desktop Client / Web Client / Mobile Apps			Desktop Client / Web Client / Mobile Apps		
	User Management	Yes	Yes	Yes	Yes	Yes	Yes
	Recording Mode	Continuous / Event / Continuous + Event / Live Only			Continuous / Event / Continuous + Event / Live Only		
	Playback Search	Multi-channel playback / Calendar - Timeline / Thumbnail / Event (VMS & web client) / Object (VMS)			Multi-channel playback / Calendar - Timeline / Thumbnail / Event (VMS & web client) / Object (VMS)		
	Clip Backup	Cloud / USB	Cloud / USB	Cloud / USB	Cloud / USB	Cloud / USB	Cloud / USB
	Mouse Included	Yes	Yes	Yes	Yes	Yes	Yes
	Power Supply	60W**	180W / 200W**	250W	500W	500W	650W
GENERAL	Power Rating	12VDC, 5A	Input: AC 100~240V, 2.5A, 50-60Hz / Input: AC 100~240V, 3.5-2.5A, 50-60Hz	Input: AC 100~240V, 3.5-1.5A, 50-60Hz	Input: AC 100~240V, 8~4A, 50-60Hz	Input: AC 100~240V, 8-4A, 50-60Hz	Input: AC 100~240V, 10-5A, 47-63Hz
	Max Power Consumption	40W	125W / 200W	170W	JBOD: Max 287W RAID: Max 311W	JBOD: Max 331W RAID: Max 370W	JBOD: Max 432W RAID: Max 450W
	PoE Switch Load	-	100W / 140W	-	-	-	-
	Max Operating Temperature	104°F (40 °C)	104°F (40 °C)	104 °F (40 °C)	104 °F (40 °C)	104 °F (40 °C)	104 °F (40 °C)
	Dedicated OS SSD Drive	Yes	Yes	Yes	Yes	JBOD: Dedicated Solid State Drive RAID: Dedicated Dual SSDs Configured as RAID 1	
RECORDER	Max Storage Configuration	40 TB	40 TB	80TB	JBOD: up to 80TB RAID: up to 48TB (36TB usable)	JBOD: 128TB RAID: 96TB (84TB usable)	JBOD: 256TB RAID: 192TB (168TB usable)
	Dimensions	W: 14.4 x H: 1.8 x D: 12.6in (366 x 44 x 316mm)	W: 8.7 x H: 1.7 x D: 10.8in (221 x 44 x 275mm) W: 11.8 x H: 1.7 x D: 11in (300 x 44 x 280mm)	W: 17.25 x H: 3.75 x D: 11.8in (428 x 95.25 x 299.72mm)	W: 16.9 x H: 3.5 x D: 18in (429.2 x 88 x 457.2mm)	W: 17.3 x H: 3.5 x D: 22in (438 x 87 x 557mm)	W: 17.2 x H: 5.2 x D: 26in (438 x 132 x 660mm)
	Unit Weight	8.2lbs (3.71kg) / 8.6lbs (3.9kg) / 9lbs (4.08kg)	3.5lbs (1.59kg) / 5lbs (2.27kg)	12.5lbs (5.67kg)	27lbs (12.25kg)	38lbs (17.2kg)	77lbs (34.9kg)
	Rack Mount	Rack Mount Ears Included	Installation Kit Included	Rack Mount Ears Included	Rack Mount Ears Included	Rack Slide Kit Included	Rack Slide Kit Included
	Country of Origin	Taiwan	Taiwan	USA	USA	USA	USA
NDAA Compliant	Yes	Yes	Yes	Yes	Yes	Yes	

*Requires performance upgrade / **External Power Supply

INDOOR IP DOME CAMERAS OUTDOOR IP DOME CAMERAS 360° IP CAMERAS PTZ IP DOME CAMERAS OUTDOOR MULTISENSOR



	OE-C101D4-S / OE-C1013D4-S	OE-C301D4-S	OE-C1012D2-S / OE-C1014D4-S	OE-C3212D4-S / OE-C3212D8-S	OE-C9112F12	OE-C8213	OE-C9912M20
Resolution	4MP	4MP	2MP / 4MP	4MP / 8MP	12MP	3MP	20MP, 4x 5MP
Lens	2.8mm / 4.0mm Fixed	2.7 ~ 13.5mm VF, AF Zoom Lens	2.8mm Fixed	2.7 ~ 13.5mm / 2.8 ~ 12mm VF, AF, Zoom Lens	1.65mm Fisheye	4.3 ~ 170mm VF, AF, Zoom Lens	2.7 ~ 13.5mm, VF, AF, Zoom Lens
Field of View	103° / 84°	101° (wide) ~ 32° (tele)	105° / 101°	104° (wide) ~ 30° (tele) / 109° (wide) ~ 31° (tele)	180°	62° (wide) ~ 2° (tele)	103° (wide) ~ 34° (tele)
Wide Dynamic Range	True WDR @ 4MP	True WDR @ 4MP	True WDR @ 2MP / True WDR @ 4MP	True WDR @ 4MP / True WDR @ 8MP	True WDR	True WDR	True WDR
IP Rating	-	-	IP67	IP67	IP66	IP66	IP66
IR Range	98'	98'	98'	131'	16'	-	131'
IK Rating	-	-	IK10	IK10	IK10	IK10	IK10
Operating Temperature	-31°F ~ 140°F (-35°C ~ 60°C) / -22°F ~ 131°F (-30°C ~ 55°C)	-31°F ~ 140°F (-35°C ~ 60°C)	-22°F ~ 140°F (-30°C ~ 60°C)	-22°F ~ 140°F (-30°C ~ 60°C)	-22°F ~ 131°F (-30°C ~ 55°C)	-40°F ~ 122°F (-40°C ~ 50°C)	-40°F ~ 131°F (-40°C ~ 55°C)
Input Voltage Type	12vDC/PoE	12vDC/PoE	12vDC/PoE	12vDC/PoE	12vDC/PoE	24vAC/PoE+	24vDC/24vAC/PoE++
Power Consumption	5W	8.7W	5W / 4.5W	7W / 9W	12vDC: 11.16W PoE: 12.95W	25.4W	40W
Dimensions	4.3 x 2.4" (108 x 61mm)	4.9 x 3.9" (126 x 100mm)	4.3 x 3.2" (109 x 81mm)	5.8 x 4.4" (148 x 111mm)	5.1" x 2.3" (130x58mm)	8.2 x 11.1" (210 x 279mm) w/ sunshield	13.9" x 13.9" x 11.6" (352 x 352 x 295mm)
Country of Origin	China	China	China	China	Taiwan	Taiwan	Taiwan
NDA Compliant	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Analytics-enabled	Yes	Yes	Yes	Yes	No	No	No

IP TURRET CAMERAS IP BULLET CAMERAS CLOUD CAMERAS



	OE-C1024T5-S	OE-C1016T2-S	OE-C3012T4-S / OE-C3012T8-S	OE-C2212B4 / OE-C2214B4	OE-C2012B4-S / OE-C2012B8-S	OE-CC51D5 / OE-CC51D8	OE-CC52B5 / OE-CC53B8
Resolution	5MP	2MP	4MP / 8MP	4MP	4MP / 8MP	5MP / 8MP	5MP / 8MP
Lens	1.68mm Fixed	2.8mm Fixed	2.7 ~ 13.5mm / 2.8 ~ 12mm VF, AF Zoom Lens	2.8 ~ 12mm VF, AF, Zoom Lens / 2.8mm Fixed Lens	2.7 ~ 13.5mm / 2.8 ~ 12mm VF, AF, Zoom Lens	2.7 ~ 13.5mm / 3 ~ 9mm VF Motorized Zoom	2.7 ~ 13.5mm / 3 ~ 9mm VF Motorized Zoom
Field of View	180°	106°	103° (wide) ~ 29° (tele) / 105° (wide) ~ 31° (tele)	86° ~ 36° / 101.5°	103° (wide) ~ 30° (tele) / 105° (wide) ~ 31° (tele)	100° (wide) ~ 30° (tele) / 115° (wide) ~ 36° (tele)	100° (wide) ~ 30° (tele) / 115° (wide) ~ 36° (tele)
Wide Dynamic Range	True WDR @ 5MP	True WDR @ 2MP	True WDR @ 4MP / True WDR @ 8MP	True WDR @ 4MP	True WDR @ 4MP / True WDR @ 8MP	DOL-HDR	DOL-HDR
IP Rating	IP67	IP67	IP67	IP67	IP67	IP67	IP67
IR Range	66'	98'	131'	164' / 98'	164'	164'	164'
IK Rating	IK10	-	IK10	-	IK10	IK10	IK10
Operating Temperature	-22°F ~ 140°F (-30°C ~ 60°C)	-22°F ~ 140°F (-30°C ~ 60°C)	-22°F ~ 140°F (-30°C ~ 60°C)	-22°F ~ 140°F (-30°C ~ 60°C)	-22°F ~ 140°F (-30°C ~ 60°C)	IR Off: -22°F ~ 140°F (-30°C ~ 60°C) IR On: -40°F ~ 122°F (-40°C ~ 50°C)	IR Off: -22°F ~ 140°F (-30°C ~ 60°C) IR On: -40°F ~ 122°F (-40°C ~ 50°C)
Input Voltage Type	12vDC/PoE	12vDC/PoE	12vDC/PoE	12vDC/PoE	12vDC/PoE	12vDC/PoE+	12vDC/PoE+
Power Consumption	5.5W	5W	7W / 8.16W	9.6W / 5.5W	8.5W / 9.5W	12vDC: 23W PoE+: 22.5W / 12vDC: 19.2W PoE+: 22W	12vDC: 29.5W PoE+: 25W
Dimensions	4.4" x 3.7" (111 x 93mm)	4.4" x 3.7" (110 x 93mm)	5.1 x 4.3" (129 x 110mm)	8.1" x 2.9" x 2.9" / 6.6" x 2.7" x 2.4" (206 x 73 x 73mm / 168 x 68 x 60mm)	9.5 x 3.4 x 3.0" (240 x 86 x 76mm)	6.1" x 4.1" (155 x 103mm)	4.6" x 4.6" x 11.6" (118 x 118 x 295mm)
Country of Origin	China	China	China	China	China	Taiwan	Taiwan
NDA Compliant	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Analytics-enabled	Yes	Yes	Yes	No	Yes	Yes	Yes